
django-easyfilters Documentation

Release 0.2

Luke Plant

June 12, 2013

CONTENTS

django-easyfilters provides a UI for filtering a Django QuerySet by clicking on links. It is similar in some ways to `list_filter` and `date_hierarchy` in Django's admin, but for use outside the admin. Importantly, it also includes result counts for the choices, and it has a bigger emphasis on intelligent display and things 'just working'.

Contents:

INSTALLATION

Install using `pip` or `easy_install`. Nothing further is required.

OVERVIEW

Suppose your `models.py` looks something like this:

```
class Book(models.Model):
    name = models.CharField(max_length=100)
    binding = models.CharField(max_length=2, choices=BINDING_CHOICES)
    authors = models.ManyToManyField(Author)
    genre = models.ForeignKey(Genre)
    price = models.DecimalField(max_digits=6, decimal_places=2)
    date_published = models.DateField()
```

(with `BINDING_CHOICES`, `Author` and `Genre` omitted for brevity).

You might want to present a list of `Book` objects, allowing the user to filter on the various fields. Assuming your `views.py` is something like this:

```
from myapp.models import Book

def booklist(request):
    books = Book.objects.all()
    return render(request, "booklist.html", {'books': books})
```

and the template is like this:

```
{% for book in books %}
    {# etc #}
{% endfor %}
```

To add the filters, in `views.py` add a `FilterSet` subclass and change the view code as follow:

```
from django_easyfilters import FilterSet
from myapp.models import Book

class BookFilterSet(FilterSet):
    fields = [
        'binding',
        'authors',
        'genre',
        'price',
    ]

def booklist(request):
    books = Book.objects.all()
    booksfilter = BookFilterSet(books, request.GET)
    return render(request, "booklist.html", {'books': booksfilter.qs,
                                              'booksfilter': booksfilter})
```

Notice that the `books` item put in the context has been replaced by `bookfilter.qs`, so that the `QuerySet` passed to the template has filtering applied to it, as defined by `BookFilterSet` and the information from the query string (`request.GET`).

The `booksfilter` item has been added to the context in order for the filters to be displayed on the template.

Then, in the template, just add `{{ booksfilter }}` to the template. `books`. You can also use pagination e.g. using `django-pagination`:

```
{% autopaginate books 20 %}
```

```
<h2>Filters:</h2>
```

```
{{ booksfilter }}
```

```
{% paginate %}
```

```
<h2>Books found</h2>
```

```
{% for book in books %}
```

```
    {# etc #}
```

```
{% endfor %}
```

Customisation of the filters can be done in various ways - see [the *FilterSet* documentation](#) for how to do this, and [the *Filters* documentation](#) for options that can be specified.

FILTERSET

class `django_easyfilters.filterset.FilterSet`

This is meant to be used by subclassing. The only required attribute is `fields`, which must be a list of fields to produce filters for. For example, given the following model definition:

```
class Book(models.Model):
    name = models.CharField(max_length=100)
    authors = models.ManyToManyField(Author)
    genre = models.ForeignKey(Genre)
    date_published = models.DateField()
```

...you could create a `BookFilterSet` like this:

```
class BookFilterSet(FilterSet):
    fields = [
        'genre',
        'authors',
        'date_published',
    ]
```

Each item in the `fields` attribute can also be a two-tuple containing first the field name and second a dictionary of options to be passed to the *filters* as keyword arguments, or a three-tuple containing the field name, a dictionary of options, and a Filter class. In this way you can override default options and the default filter type used e.g.:

```
from django_easyfilters.filters import ValuesFilter

class BookFilterSet(FilterSet):
    fields = [
        ('genre', dict(order_by_count=True)),
        ('date_published', {}, ValuesFilter),
    ]
```

This also allows *custom Filter classes* to be used.

To use the `BookFilterSet`, please see [the overview instructions](#). The public API of `FilterSet` for use consists of:

__init__ (*queryset, params*)

`queryset` must be a `QuerySet`, which can already be filtered.

`params` must be a `QueryDict`, normally `request.GET`.

qs

This attribute contains the input `QuerySet` filtered according to the data in `params`.

In addition, there are methods/attributes that can be overridden to customise the `FilterSet`:

get_template (*field_name*)

This method is called for each field in the filterset, with the field name being passed in.

It is expected to return a Django Template instance. This template will then be rendered with the following Context data:

- **filterlabel** - the label for the filter (derived from `verbose_name` of the field)
- **choices** - a list of *choices* for the filter. Each one has the following attributes:
 - **link_type**: either `remove`, `add` or `display`, depending on the type of the choice.
 - **label**: the text to be displayed for this choice.
 - **url** for those that are `remove` or `add`, a URL for selecting that filter.
 - **count**: for those that are `add` links, the number of items in the `QuerySet` that match that choice.

template

A string containing a Django template, used to render all the filters. It is used by the default `get_template` method, see above.

FILTERS

When you specify the `fields` attribute on a `FilterSet` subclass, various different `Filter` classes will be chosen depending on the type of field. They are listed below, with the keyword argument options that they take.

class `django_easyfilters.filters.Filter`

This is the base class for all filters, and has provides some options:

- `query_param`:

The parameter in the query string that will be used for this field. This can be useful for shortening the query strings that are generated.

- `order_by_count`:

Default: `False`

If `True`, this will cause the choices to be sorted so that the choices with the largest ‘count’ appear first.

class `django_easyfilters.filters.ForeignKeyFilter`

This is used for `ForeignKey` fields

class `django_easyfilters.filters.ManyToManyFilter`

This is used for `ManyToMany` fields

class `django_easyfilters.filters.ChoicesFilter`

This is used for fields that have ‘choices’ defined. The choices presented will be in the order specified in ‘choices’.

class `django_easyfilters.filters.DateTimeFilter`

This is the most complex of the filters, as it allows drill-down from year to month to day. It takes the following options:

- `max_links`

Default: `12`

The maximum number of links to display. If the number of choices at any level does not fit into this value, ranges will be used to shrink the number of choices.

- `max_depth`

Default: `None`

If ‘year’ or ‘month’ is specified, the drill-down will be limited to that level.

class `django_easyfilters.filters.NumericRangeFilter`

This filter produces ranges of values for a numeric field. It is the default filter for decimal fields, but can also be used with integer fields. It attempts to make the ranges ‘look nice’ using rounded numbers in an automatic way. It uses ‘drill-down’ like `DateTimeFilter`.

It takes the following options:

- `max_links`

Default: 5

The maximum number of links to display. If there fewer distinct values than this in the data, single values will be shown, otherwise ranges.

- `ranges`

Default: None

If this is specified, it will override the (initial) automatic range. The value should be a list of ranges, where each item in the list is either:

- a two-tuple containing the beginning and end range values
- a three-tuple containing the beginning and end range values and a custom label.

- `drilldown`

Default: True

If `False`, only one level of choices will be displayed.

The ‘end points’ of ranges are handled in the following way: the lower bound is exclusive, and the upper bound is inclusive, apart from for the first range, where both are inclusive. This is designed for a fairly intuitive behaviour.

class `django_easyfilters.filters.ValuesFilter`

This is the fallback that is used when nothing else matches.

4.1 Custom Filter classes

As described in the `FilterSet` documentation, you can provide your own `Filter` class for a field. If you do so, it is expected to have the following API:

- `__init__(field, model, params, **kwargs)`

Constructor. `field` is the string identifying the field, `model` is the model class, `params` is a `QueryDict` (i.e. `request.GET`). `kwargs` contains any custom options specified for the filter.

- `apply_filter(qs)`

This method takes the `QuerySet` `qs` and returns a `QuerySet` that has filters applied to it, where the filter parameters are defined in the `params` that were passed to the constructor. The method must be able to extract the relevant parameter, if it exists, and filter the `QuerySet` accordingly.

- `get_choices(qs)`

This method is passed a fully filtered `QuerySet`, and must return a list of choices to present to the user. The choices should be instances of `django_easyfilters.filters.FilterChoice`, which has the attributes:

- `label`: User presentable text string for the choice
- `link_type`: choice of `FILTER_ADD`, `FILTER_REMOVE`, `FILTER_DISPLAY`
- `count`: the number of items for this choice (only for `FILTER_ADD`)
- `params`: parameters used to create a link for this option, as a `QueryDict`

At the moment, all other methods of `Filter` and subclasses are considered private implementation details. You can subclass `Filter` if you want, and use its functionality, but it may change without warning.

DEVELOPMENT

Python 2.6 is required for running the test suites and demo app.

First, ensure the directory containing the `django_easyfilters` directory is on your Python path (virtualenv recommended). Django is a required dependency.

5.1 Tests

To run the test suite, do:

```
./manage.py test django_easyfilters
```

5.2 Editing test fixtures

To edit the test fixtures, you can edit the fixtures in `django_easyfilters/tests/fixtures/`, or you can do it via an admin interface:

First create an empty db:

```
rm tests.db  
./manage.py syncdb
```

Then load with current test fixture:

```
./manage.py loaddata django_easyfilters_tests
```

Then edit in admin at <http://localhost:8000/admin/>

```
./manage.py runserver
```

Or from a Python shell.

Then dump data:

```
./manage.py dumpdata tests --format=json --indent=2 > django_easyfilters/tests/fixtures/django_easyf...
```

5.3 Demo

Once the test fixtures have been loaded into the DB, and the devserver is running, as above, you can view a test page at <http://localhost:8000/books/>

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*